


28-03803

NO	DESCRIPTION	DATE	BY
A	MEC 06045	07/28/06	DW

TOP MOUNTING DIMENSIONS FOR MODEL NO. 3T-3900



A, B & C (B.C.) = MOUNTING PAD SPACING
 D = THREAD OF MOUNTING HOLES
 G = ACROSS FLAT ON STEM
 L = DISTANCE TO TOP OF STEM FROM MOUNTING PAD

VALVE SIZE	DIMENSIONS (INCHES)							
	A	B	C (B.C.)	D (THREAD)	MTG PATTERN	G	L	M
1/4-3/8	1.004	1.004	∅1.42	M5	F03	0.197	0.677	0.492
1/2	1.004	1.004	∅1.42	M5	F03	0.236	0.846	0.531
3/4	1.004	1.004	∅1.42	M5	F03	0.236	0.780	0.531
1	1.168	1.168	∅1.65	M6	F04	0.315	0.988	0.705
1 1/2	1.392	1.392	∅1.97	M6	F05	0.315	1.028	0.708
2	1.952	1.952	∅2.76	M8	F07	0.472	1.200	0.728



MARWIN
Ball Valves

RICHARDS INDUSTRIES
 3170 Wasson Rd.
 Cincinnati, Ohio 45209
 Telephone (513) 533-5600
 Fax (513) 533-7343

DR. BY	DW	03/23/05
CHK. BY		

28-03803