



1 MANUAL OVER-RIDE HANDWHEEL LOCATED ON TOP FOR ACTUATORS ER-6-15-4, ER-20-12-4 AND ER-38-14-4.

2 MANUAL OVER-RIDE HANDWHEEL LOCATED ON SIDE FOR ACTUATOR ER-50-68-4 & ER-70-68-4.

3L/T-2S33-150/300 FULL PORT WITH ELECTRIC ACTUATOR

SIZE	ACTUATOR	DIMENSIONS (INCHES)									WT.(LBS)	
		A	B	C	D	F	G (150#)	G*(300#)	H	J	150#	300#
2"	ER-6-15-4	8.66	12.35	7.00	7.00	7.20	3.00	3.25	4.33	5.1X3.4	51	60
2.5"	ER-15-30-4	11.02	12.94	7.00	7.00	7.20	3.50	3.74	5.51	5.1X3.4	73	84
3"	ER-38-14-4	11.22	17.60	10.00	10.00	9.31	3.74	4.13	5.61	Ø7.00	106	128
4"	ER-50-68-4	13.66	22.42	14.00	12.90	13.50	4.51	5.00	6.83	Ø7.00	252	274
6"	ER-70-68-4	16.93	25.80	14.00	12.90	13.50	5.50	6.22	8.46	Ø7.00	419	-

MAX. DIFF. PRESSURE ACROSS VALVE

SEAT MATERIAL-RPTFE

DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"

OTHER VA. DIM.: ≤NPS 2", ± 1/8"

NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"

VA-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 2"-6" 3L/3T-2S33F-150/300

FULL PORT W/ER ELECTRICAL ACTUATOR

CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 05/03/11

CHK.BY

MD02019