


△ 1 MANUAL OVR-SIDE HANDWHEEL LOCATED ON TOP FOR ACTUATORS ER-6-15-4, ER-20-12-4 AND ER-38-14-4.

△ 2 MANUAL OVR-SIDE HANDWHEEL LOCATED ON SIDE FOR ACTUATOR ER-50-08-4 & ER-70-08-4.



3L/T-2533-150/300 FULL PORT WITH ELECTRIC ACTUATOR

SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT(LBS)	
		A	B	C	D	F	G	G(150#)	G(300#)	H	J	150#	300#
2"	ER-6-15-4	8.66	12.35	7.60	7.00	7.26	3.00	3.35	4.38	5.133.4	5.1	60	60
2.5"	ER-15-30-4	11.02	13.94	7.90	7.00	7.26	3.50	3.74	5.31	5.133.4	7.9	94	94
3"	ER-38-14-4	11.22	17.69	10.00	10.00	9.31	3.74	4.13	5.61	87.00	106	128	128
4"	ER-50-08-4	13.66	22.42	14.00	12.90	13.90	4.51	5.00	6.68	87.00	263	274	274
6"	ER-70-08-4	16.09	25.80	14.00	12.90	13.90	5.50	6.32	8.46	87.00	419	-	-

MAX. DIFF. PRESSURE ACROSS VALVE

SEAT MATERIAL:PTFE

DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 3L/T-2533-150/300, 274-677

VALVE ELECTRICAL ACTUATOR _____

CERTIFIED _____ DATE _____



a division of Ingersoll Rand

CINCINNATI, OHIO U.S.A.

www.marwinvalve.com

DL BY DW BMM

CHKY

MD02019