



SIZE	ACTUATOR	DIMENSIONS (INCHES)											WT.(LBS)		
		A	B	C	D	E 150#	E 300#	F	G	H	J	K	L	150#	300#
2"	UT-2.5-DA	8.66	10.21	9.4	4.2	3.00	3.25	3.15	2.00	4.27	0.79	2.3	4.33	45	54
	UT-3.5-SR		11.88	12.9	5.4					5.57	1.18	2.9		60	69
2.5"	UT-3-DA	11.02	12.89	10.7	4.8	3.50	3.74	3.82	3.50	4.78	0.79	2.7	5.51	70	81
	UT-5-SR		15.90	20.6	7.4					7.40	1.18	3.9		89	124
3"	UT-3.5-DA	11.22	14.50	12.9	5.4	3.74	4.13	4.25	3.50	5.57	1.18	2.9	5.61	91	113
	UT-5-SR		16.83	20.6	7.4				4.00	7.40	1.18	3.9		127	149
4"	UT-5-DA	13.66	17.66	20.6	7.4	4.51	5.00	5.08	4.00	7.40	1.18	3.9	6.83	177	199
	UT-6-SR		19.67	22.6	8.6					9.41	1.18	4.3		252	274
6"	UT-6-DA	18.90*	23.05	22.6	8.6	5.50	6.22	8.46	4.00	9.41	1.18	4.3	9.45*	385	
	UT-7-SR		26.67	26.5	11.4					13.03	1.18	5.7		511	

*DIM 'A' IS 21.65" & 'L' IS 10.83" FOR 300#

SEAT MATERIAL-RPTFE
MAX. DIFF. PRESSURE ACROSS VALVE

TOL. UNLESS OTHERWISE NOTED (IN.)
 VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"
 VA-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 2"-6" 3L/3T-2S33F FULL PORT
 150/300 W/UT_PNEUMATIC (NEW) @80PSI
 CERTIFIED _____ DATE _____

 **MARWINVALVE**
 a division of Richards Industries
 CINCINNATI, OHIO U.S.A.
 www.marwinvalve.com

DR. BY	DW	05/03/11	MD02037
CHK.BY			