


SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
2"	UT-2-DA	7.01	9.23	8.2	3.7	3.00	2.62	2.00	3.82	0.79	2.1	25.8
	UT-3-SR		10.19	10.7	4.8				4.78	0.79	2.7	34.2
3"	UT-3-DA	7.94	12.80	10.7	4.8	3.75	3.73	3.50	4.78	0.79	2.7	47.4
	UT-5-SR		15.81	20.6	7.4				7.40	1.18	3.9	90.0
4"	UT-3.5-DA	9.02	14.46	12.9	5.4	4.51	4.21	3.50	5.57	1.18	2.9	71.9
	UT-5-SR		16.29	20.6	7.4				7.40	1.18	3.9	108

DIFF. PRESSURE ACROSS VALVE=275PSI
SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 2"-4" STANDARD PORT SER. 2000
 UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____

 MARWIN Ball Valves	RICHARDS INDUSTRIES 3170 Wasson Rd. Cincinnati, Ohio 45209 Telephone (513) 533-5600 Fax (513) 533-7343	
	DR. BY	DW 03/19/03
CHK.BY		MD02043