



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1"	UT-0-DA	5.00	7.20	5.5	2.8	2.13	1.67	2.00	2.74	0.79	1.6	12.9
	UT-2-SR		8.28	8.2	3.7				3.82	0.79	2.1	
1 1/2"	UT-1-DA	6.50	8.18	6.4	3.2	2.50	2.22	2.00	3.17	0.79	1.8	17.7
	UT-2.5-SR		9.28	9.4	4.2				4.27	0.79	2.3	
2"	UT-2-DA	7.01	9.23	8.2	3.7	3.00	2.62	2.00	3.82	0.79	2.1	25.8
	UT-3-SR		10.19	10.7	4.8				4.78	0.79	2.7	
3"	UT-3-DA	7.94	12.80	10.7	4.8	3.75	3.73	3.50	4.78	0.79	2.7	47.4
	UT-4.5-SR (A)		15.31	16.9	6.5				6.90	1.18	3.4	
4"	UT-3.5-DA	9.02	14.46	12.9	5.4	4.51	4.21	3.50	5.57	1.18	2.9	71.9
	UT-5-SR		16.29	20.6	7.4				7.40	1.18	3.9	

DIFF. PRESSURE ACROSS VALVE=275PSI

SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"

OTHER VA. DIM.: ≤NPS 2", ± 1/8";

NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"

VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

TAG No. \_\_\_\_\_

SIZE & MODEL # 2"-4" REDUCED PORT SER. 2000R

UT (NEW STYLE) ACT, @80PSI PRESSURE

CERTIFIED \_\_\_\_\_ DATE \_\_\_\_\_



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 01/24/11

CHK.BY

MD02043