



TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}''$
 OTHER VA. DIM.: $\leq \text{NPS } 2'', \pm \frac{1}{8}''$;
 NPS $2 \frac{1}{2}'' \sim 4'', \pm \frac{1}{4}''$; $> 4'', \pm \frac{1}{2}''$
 VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}''$

SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1 1/2"	UT-2-DA	7.50	9.19	8.2	3.7	3.06	2.58	2.00	3.82	0.79	2.1	27.5
	UT-3-SR		10.15	10.7	4.8				4.78	0.79	2.7	36.4
2"	UT-2.5-DA	8.50	9.99	9.4	4.2	3.25	2.93	2.00	4.27	0.79	2.3	33.8
	UT-3.5-SR		11.68	12.9	5.4				5.57	1.18	2.9	48.7
2 1/2"	UT-3.5-DA	9.50	13.79	12.9	5.4	3.75	3.54	3.50	5.57	1.18	2.9	63.1
	UT-5-SR		16.12	20.6	7.4			4.00	7.40	1.18	3.9	99.2
3"	UT-3.5-DA	11.12	14.18	12.9	5.4	4.12	3.93	3.50	5.57	1.18	2.9	84.5
	UT-5-SR		16.51	20.6	7.4			4.00	7.40	1.18	3.9	120.6
4"	UT-5-DA	12.00	17.38	20.6	7.4	5.00	4.80	4.00	7.40	1.18	3.9	145.5
	UT-6-SR		19.39	22.6	8.6			4.00	9.41	1.18	4.3	213.3

DIFF. PRESSURE ACROSS VALVE=720PSI

SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1.5"-4" FULL PORT SER. 2000-F3

UT (NEW STYLE) ACT, @80PSI PRESSURE

CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 08/30/04

CHK. BY _____

MD02045