

SIZE	ACTUATOR	DIMENSIONS (INCHES)											WT (LBS)
		A	B	C	D	E	F	G	H	J	K	L	
3/8"	UT-0-DA	2.80	7.05	5.5	2.8	1.40	1.52	1.40	2.74	0.79	1.6	2.00	7.7
	UT-1-SR		7.48	6.4	3.2				3.17	0.79	1.8		9.4
1/2"	UT-0-DA	3.33	7.19	5.5	2.8	1.67	1.66	1.67	2.74	0.79	1.6	2.00	9.9
	UT-2-SR		8.27	8.2	3.7				3.82	0.79	2.1		14.6
3/4"	UT-0-DA	3.57	7.58	5.5	2.8	1.79	2.05	1.79	2.74	0.79	1.6	2.00	12.1
	UT-2-SR		8.66	8.2	3.7				3.82	0.79	2.1		16.8
1"	UT-1-DA	4.07	8.14	6.4	3.2	2.04	2.18	2.04	3.17	0.79	1.8	2.00	15.3
	UT-2.5-SR		9.24	9.4	4.2				4.27	0.79	2.3		21.5
1 1/4"	UT-1-DA	5.55	8.60	6.4	3.2	2.78	2.64	2.78	3.17	0.79	1.8	2.00	17.5
	UT-2.5-SR		9.70	9.4	4.2				4.27	0.79	2.3		23.7
1 1/2"	UT-2-DA	6.14	9.58	8.2	3.7	3.07	2.97	3.07	3.82	0.79	2.1	2.00	27.6
	UT-3.5-SR		11.72	12.9	5.4				5.57	1.18	2.9		44.4

MAX. DIFF. PRESSURE ACROSS VALVE

SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

- VA. END-TO-END LENGTH: ± 1/16"
- OTHER VA. DIM.: ≤NPS 2", ± 1/8"
- NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"
- VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____


CUSTOMER _____

TAG No. _____

SIZE & MODEL # 3/8"-1 1/2" 3L/T-2QF

FULL PORT W/UT (NEW STYLE) ACT, @80PSI

CERTIFIED _____ DATE _____



MARWINVALVE

a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY	DW	05/03/11	MD02047
CHK.BY			