



▲ **1** MANUAL OVER-RIDE HANDWHEEL PROVIDED ON ACTUATORS ER-6-15-4, ER-10-15-4, ER-15-30-4, ER-20-12-4 AND ER-30-14-4 (TOP ONLY).

▲ **2** MANUAL OVER-RIDE HANDWHEEL PROVIDED ON ACTUATOR ER-70-08-4 (SIDE ONLY).

SIZE	ACTUATOR	DIMENSIONS (INCHES)											WT.(LBS)
		A	B	C	D	E	F	G	H				
1"	ER-6-15-4	6.50	12.08	7.00	7.00	2.12	3.15	-	4.0	-	34		
1 1/2"	ER-10-15-4	7.62	13.08	7.00	7.00	2.59	3.75	-	4.0	-	44		
2"	ER-15-30-4	8.00	13.08	7.00	7.00	3.09	4.10	-	4.0	-	53		
3"	ER-20-12-4	9.50	16.48	9.25	9.25	3.75	4.75	-	6.0	-	102		
4"	ER-30-14-4	13.36	17.31	9.25	9.25	4.59	6.20	-	6.0	-	144		
6"	ER-70-08-4	17.70	24.12	14.00	12.88	5.59	8.00	4.31	7.0	-	255		

MAX. DIFF. PRESSURE ACROSS VALVE
SEAT MATERIAL: NPTFE
DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # **1"-6" FULL PORT SER. 31/75-9K**
 SER ELECTRIC ACTUATOR
 CERTIFIED _____ DATE _____



DL BY DW BMM MD02053
 CHRY