



1 MANUAL OVER-RIDE HANDWHEEL PROVIDED ONLY ON ACTUATOR ER-6-15-4 (ON TOP).

SIZE	ACTUATOR	DIMENSIONS (INCHES)							WT.(LBS)
		A	B	C	D	E	F	G	
3/8"	ER-2-5-4	2.80	8.90	6.88	4.25	1.40	3.0	1.40	11
1/2"	ER-2-5-4	3.33	9.04	6.88	4.25	1.67	3.0	1.67	13
3/4"	ER-2-5-4	3.57	9.43	6.88	4.25	1.79	3.0	1.79	15
1"	ER-3-5-4	4.07	9.56	6.88	4.25	2.04	3.0	2.04	18
1 1/4"	ER-3-5-4	5.55	10.02	6.88	4.25	2.78	3.0	2.78	20
1 1/2"	ER-6-15-4	6.14	11.67	7.00	7.00	3.07	4.0	3.07	35

MAX. DIFF. PRESSURE ACROSS VALVE
 SEAT MATERIAL-RPTFE
 DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}''$
 OTHER VA. DIM.: $\leq \text{NPS } 2'', \pm \frac{1}{8}''$;
 NPS 2 $\frac{1}{2}'' \sim 4'', \pm \frac{1}{4}''$; $> 4'', \pm \frac{1}{2}''$
 VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}''$

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 3/8"-1 1/2" 3L/T-2QF
FULL PORT W/ER ELECTRIC ACTUATOR
 CERTIFIED _____ DATE _____

 **MARWINVALVE**
 a division of Richards Industries
 CINCINNATI, OHIO U.S.A
 www.marwinvalve.com

DR. BY	DW	05/03/11	MD02054
CHK.BY			