



TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}''$
 OTHER VA. DIM.: $\leq \text{NPS } 2'', \pm \frac{1}{8}''$
 NPS 2 $\frac{1}{2}'' \sim 4'', \pm \frac{1}{4}''$; $> 4'', \pm \frac{1}{2}''$
 VA-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}''$

SIZE REDUCED	ACTUATOR	DIMENSIONS (INCHES)					WT.(LBS)
		A	B	C	D	E	
1/2"	UT-0-DA	5.50	6.34	6.81	2.80	1.00	10
	UT-0-SR		6.34	6.81	2.80		10
3/4"	UT-0-DA	6.00	6.42	6.81	2.80	1.05	11
	UT-1-SR		6.85	7.72	3.17		13
1"	UT-1-DA	6.50	7.01	7.72	3.17	1.30	14
	UT-2-SR		7.01	9.55	3.17		16
1 1/4"	UT-1-DA	7.00	7.70	7.72	3.17	1.45	16
	UT-2-SR		7.70	9.55	3.17		18
1 1/2"	UT-2-DA	7.50	7.93	9.55	3.17	1.68	19
	UT-2.5-SR		8.92	9.84	4.17		24
2"	UT-2-DA	8.50	8.08	9.55	3.17	1.83	23
	UT-2.5-SR		9.07	9.84	4.17		28
2 1/2"	UT-2.5-DA	9.50	9.54	9.84	4.17	2.62	35
	UT-3-SR		10.05	11.69	4.84		42
3"	UT-3-DA	11.12	10.45	11.69	4.84	2.95	46
	UT-3.5-SR		11.27	13.58	5.39		60
4"	UT-3.5-DA	12.00	12.01	13.58	5.39	3.69	62
	UT-4-SR		12.45	15.91	5.83		74

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-4" 3000/7000 RED. PORT
WITH PNEUMATIC ACUTATOR, EXT. BSE/FSW ENDS
 CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY JLW 12/03/01

CHK.BY

MD03062