



| SIZE | ACTUATOR | DIMENSIONS (INCHES) | | | | | | | | | | | WT (LBS) |
|----------------|-----------|---------------------|------|-----|------|------|------|------|------|-----|------|------|-------------|
| | | A | B | C | D | E | F | G | H | J | K | L | |
| 1/4" & 3/8" | UF-0-DA | 6.59 | 5.5 | 2.8 | 0.63 | 1.06 | 1.94 | 2.24 | 0.79 | 1.6 | 2.00 | 9.2 | |
| | UF-3-SR | 7.67 | 8.2 | 3.7 | | | | 3.62 | 0.79 | 2.1 | 2.00 | 16.7 | |
| 1/2" | UF-0-DA | 6.73 | 5.5 | 2.8 | 0.74 | 1.20 | 1.48 | 2.24 | 0.79 | 1.6 | 2.00 | 9.2 | |
| | UF-3-SR | 7.81 | 8.2 | 3.7 | | | | 3.62 | 0.79 | 2.1 | 2.00 | 16.7 | |
| 3/4" | UF-1-DA | 7.41 | 6.4 | 3.2 | 0.94 | 1.45 | 1.69 | 3.17 | 0.79 | 1.8 | 2.00 | 11.2 | |
| | UF-3-SR | 8.06 | 8.2 | 3.7 | | | | 3.62 | 0.79 | 2.1 | 2.00 | 17.3 | |
| 1" | UF-3-DA | 8.16 | 8.2 | 3.7 | 1.10 | 1.95 | 2.68 | 3.62 | 0.79 | 2.1 | 2.00 | 15.5 | |
| | UF-3-SR | 9.12 | 10.7 | 4.8 | | | | 4.26 | 0.79 | 2.7 | 2.00 | 29.3 | |
| 1 1/4" | UF-3-DA | 9.32 | 8.2 | 3.7 | 1.26 | 1.71 | 3.26 | 3.62 | 0.79 | 2.1 | 2.00 | 15.8 | |
| | UF-3-SR | 9.28 | 10.7 | 4.8 | | | | 4.26 | 0.79 | 2.7 | 2.00 | 24.6 | |
| 1 1/2" | UF-3-DA | 8.74 | 8.2 | 3.7 | 1.59 | 2.13 | 2.46 | 3.62 | 0.79 | 2.1 | 2.00 | 17.8 | |
| | UF-3.5-SR | 10.88 | 12.9 | 5.4 | | | | 5.57 | 1.18 | 2.9 | 2.00 | 32.2 | |
| 2" | UF-3.5-DA | 9.51 | 9.4 | 4.2 | 1.86 | 2.48 | 2.87 | 4.27 | 0.79 | 2.3 | 2.00 | 26.2 | |
| | UF-3.5-SR | 11.29 | 12.9 | 5.4 | | | | 5.57 | 1.18 | 2.9 | 2.00 | 39.5 | |

MAX. DIFF. PRESSURE ACROSS VALVE
SEAT MATERIAL-PP/TFE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4"-2" STD. PORT ST-337
 BALL/W/OUT NEW STYLE ACT. @60PSI PRESSURE
 CERTIFIED _____ DATE _____



CINCINNATI, OHIO U.S.A.

www.marwinvalve.com

DA:BY DW:MM/IN CH:KTY

MD03093