



TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8"
 NPS 2 1/2"-4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	2.91	6.77	5.5	2.8	1.00	1.24	2.00	2.74	0.79	1.6	9.6
	UT-1-SR		7.20	6.4	3.2				3.17	0.79	1.8	10.8
3/4"	UT-0-DA	3.17	6.84	5.5	2.8	1.05	1.31	2.00	2.74	0.79	1.6	10.6
	UT-1-SR		7.27	6.4	3.2				3.17	0.79	1.8	12.3
1"	UT-0-DA	3.87	7.08	5.5	2.8	1.30	1.55	2.00	2.74	0.79	1.6	12.5
	UT-2-SR		8.16	8.2	3.7				3.82	0.79	2.1	17.4
1 1/4"	UT-1-DA	4.36	7.41	6.4	3.2	1.45	1.45	2.00	3.17	0.79	1.8	15.3
	UT-2.5-SR		8.51	9.4	4.2				4.27	0.79	2.3	19.8
1 1/2"	UT-2-DA	4.86	8.29	8.2	3.7	1.68	1.68	2.00	3.82	0.79	2.1	19.8
	UT-3-SR		9.25	10.7	4.8				4.78	0.79	2.7	28.6
2"	UT-2-DA	5.50	8.44	8.2	3.7	1.83	1.83	2.00	3.82	0.79	2.1	23.8
	UT-3.5-SR		10.58	12.9	5.4				5.57	1.18	2.9	40.5
2 1/2"	UT-3.5-DA	5.59	10.66	12.9	5.4	2.62	2.30	2.00	5.57	1.18	2.9	44.6
	UT-5-SR		12.88	20.6	7.4				7.40	1.18	3.9	80.5
3"	UT-5-DA	8.98	13.28	14.4	7.4	2.95	2.70	2.00	7.40	1.18	3.9	73.7
	UT-6-SR		15.29	22.6	8.6				9.41	1.18	4.3	135.5
4"	UT-5-DA	8.78	14.02	20.6	7.4	3.69	3.44	2.00	7.40	1.18	3.9	87.0
	UT-6-SR		16.03	22.6	8.6				9.41	1.18	4.3	144.7

1 DIFF. PRESSURE ACROSS VALVE=1000PSI

SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1/2"-4" STD. PORT SER. 3000R

W/UT (NEW STYLE) ACT, @80PSI PRESSURE

CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 06/01/04

CHK.BY

MD03100