



TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}''$
 OTHER VA. DIM.: $\leq \text{NPS } 2'', \pm \frac{1}{8}''$
 NPS $2 \frac{1}{2}'' \sim 4'', \pm \frac{1}{4}''$; $> 4'', \pm \frac{1}{2}''$
 VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}''$

SIZE	ACTUATOR	DIMENSIONS (INCHES)								
		A	B	C	D	F	G	H	J	K
1/2"	UT-0-DA	4.25	6.77	5.5	2.8	1.24	2.00	2.74	0.79	1.6
	UT-1-SR		7.20	6.4	3.2			3.17	0.79	1.8
3/4"	UT-0-DA	4.62	6.84	5.5	2.8	1.31	2.00	2.74	0.79	1.6
	UT-1-SR		7.27	6.4	3.2			3.17	0.79	1.8
1"	UT-0-DA	5.00	7.08	5.5	2.8	1.55	2.00	2.74	0.79	1.6
	UT-2-SR		8.16	8.2	3.7			3.82	0.79	2.1
1 1/4"	UT-1-DA	5.50	7.41	6.4	3.2	1.45	2.00	3.17	0.79	1.8
	UT-2.5-SR		8.51	9.4	4.2			4.27	0.79	2.3
1 1/2"	UT-2-DA	6.50	8.29	8.2	3.7	1.68	2.00	3.82	0.79	2.1
	UT-3-SR		9.25	10.7	4.8			4.78	0.79	2.7
2"	UT-2-DA	7.00	8.44	8.2	3.7	1.83	2.00	3.82	0.79	2.1
	UT-3.5-SR		10.58	12.9	5.4			5.57	1.18	2.9
2 1/2"	UT-3.5-DA	7.50	10.66	12.9	5.4	2.30	2.00	5.57	0.79	2.9
	UT-5-SR		12.88	20.6	7.4			7.40	1.18	3.9
3"	UT-4-DA	8.00	11.92	14.4	5.8	2.70	2.00	6.04	1.18	3.2
	UT-6-SR		15.29	22.6	8.6			9.41	1.18	4.3
4"	UT-5-DA	9.00	14.02	20.6	7.4	3.44	2.00	7.40	1.18	3.9
	UT-6-SR		16.03	22.6	8.6			9.41	1.18	4.3

1 DIFF. PRESSURE ACROSS VALVE=1000PSI

SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1/2"-4" STD. PORT SER. 3000

W/UT (NEW STYLE) ACT, #150 F.E, @80PSI PR.

CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 04/08/04
 CHK.BY

MD03135