

SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	2.50	6.00	5.5	2.8	0.90	0.62	1.85	2.74	0.79	1.6	8.6
	UT-1-SR		6.43	6.4	3.2				3.17	0.79	1.8	
3/4"	UT-0-DA	3.00	6.13	5.5	2.8	0.97	0.75	1.85	2.74	0.79	1.6	8.6
	UT-1-SR		6.56	6.4	3.2				3.17	0.79	1.8	
1"	UT-1-DA	3.69	6.65	6.4	3.2	1.25	0.84	1.85	3.17	0.79	1.8	10.6
	UT-2.5-SR		7.75	9.4	4.2				4.27	0.79	2.3	
1 1/4"	UT-1-DA	4.09	6.65	6.4	3.2	1.34	0.84	1.85	3.17	0.79	1.8	12.6
	UT-2.5-SR		7.75	9.4	4.2				4.27	0.79	2.3	
1 1/2"	UT-1-DA	4.56	7.22	6.4	3.2	1.50	1.00	2.26	3.17	0.79	1.8	13.5
	UT-3-SR		8.83	10.7	4.8				4.78	0.79	2.7	
2"	UT-1-DA	6.16	7.43	9.4	3.2	2.00	1.19	2.28	3.17	0.79	1.8	19.5
	UT-3-SR		9.04	10.7	4.8				4.78	0.79	2.7	
2 1/2"	UT-2-DA	6.84	8.05	8.2	3.7	2.50	1.56	2.50	3.82	0.79	2.1	35.7
	UT-3.5-SR		10.81	12.9	5.4				5.57	1.18	2.9	

DIFF. PRESSURE ACROSS VALVE=600PSI

SEAT MATERIAL-TEFLON


CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1/2"-2 1/2" STD. PORT 4600
W/UT (NEW STYLE) ACT, @80PSI PRESSURE

CERTIFIED _____ DATE _____

 MARWIN Ball Valves			RICHARDS INDUSTRIES 3170 Wasson Rd. Cincinnati, Ohio 45209 Telephone (513) 533-5600 Fax (513) 533-7343	
			DR. BY	DW
CHK. BY				