

SIZE	ACTUATOR	DIMENSIONS (INCHES)						WT.(LBS)
		A	B	C	D	E	F	
1/2"	ER-1-2-4	2.50	6.97	5.63	4.00	0.90	2.5	11
3/4"	ER-1-2-4	3.00	7.10	5.63	4.00	0.97	2.5	13
1"	ER-3-5-4	3.69	8.07	6.88	4.25	1.25	3.0	15
1 1/4"	ER-3-5-4	4.09	8.07	6.88	4.25	1.34	3.0	16
1 1/2"	ER-4-10-4	4.56	10.00	7.00	7.00	1.50	4.0	25
2"	ER-4-10-4	6.16	10.21	7.00	7.00	2.00	4.0	29
2 1/2"	ER-6-15-4	6.84	10.80	7.00	7.00	2.50	4.0	39


1 MANUAL OVER-RIDE HANDWHEEL PROVIDED ONLY ON ACTUATORS ER-4-10-4 & ER-6-15-4 (ON TOP).

DIFF. PRESSURE ACROSS VALVE=600PSI

SEAT MATERIAL-TEFLON

DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

CUSTOMER ORDER # \_\_\_\_\_  
 CUSTOMER \_\_\_\_\_  
 TAG No. \_\_\_\_\_  
 SIZE & MODEL # 1/2"-2 1/2" STD. PORT 4600  
 W/ER ELECTRIC ACTUATOR  
 CERTIFIED \_\_\_\_\_ DATE \_\_\_\_\_

 <b>MARWIN</b> Ball Valves		RICHARDS INDUSTRIES 3170 Wasson Rd. Cincinnati, Ohio 45209 Telephone (513) 533-5600 Fax (513) 533-7343	
		DR. BY	DW
CHK.BY			