



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	4.25	6.94	5.5	2.8	1.75	0.91	2.50	2.74	0.79	1.6	5.8
	UT-2-SR		8.02	8.2	3.7				3.82	0.79	2.1	10.6
3/4"	UT-0-DA	4.62	7.11	5.5	2.8	1.94	1.08	2.50	2.74	0.79	1.6	6.5
	UT-2-SR		8.19	8.2	3.7				3.82	0.79	2.1	11.3
1"	UT-1-DA	5.00	8.07	6.4	3.2	2.12	1.61	2.50	3.17	0.79	1.8	8.2
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	14.4
1 1/2"	UT-1-DA	6.50	8.07	6.4	3.2	2.50	2.11	2.00	3.17	0.79	1.8	16.2
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	22.4
2"	UT-2-DA	7.00	9.03	8.2	3.7	3.00	2.42	2.00	3.82	0.79	2.1	23.5
	UT-3-SR		9.99	10.7	4.8				4.78	0.79	2.7	32.3
3"	UT-3-DA	8.00	12.89	10.7	4.8	3.75	3.82	3.50	4.78	0.79	2.7	52.6
	UT-5-SR		15.90	20.6	7.4				7.40	1.18	3.9	95.3
4"	UT-3.5-DA	9.00	15.25	12.9	5.4	4.50	5.00	3.50	5.57	1.18	2.9	81.1
	UT-5-SR		17.08	20.6	7.4				7.40	1.18	3.9	117
6"	UT-5-DA	10.50	18.80	20.6	7.4	5.50	6.22	4.00	7.40	1.18	3.9	167
	UT-6-SR		20.81	22.6	8.6				9.41	1.18	4.3	235
8"	UT-6-DA	11.50	21.87	22.6	8.6	6.75	7.28	4.00	9.41	1.18	4.3	270
	UT-7-SR		25.49	26.5	11.4				13.03	1.18	5.7	395
10"	UT-7-DA	13.00	27.38	26.5	11.4	8.00	9.17	4.00	13.03	1.18	5.7	457

DIFF. PRESSURE ACROSS VALVE=285PSI
SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-10" RED. PORT SER. 5000R
UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____



DR. BY	DW	01/21/11	MD05008
CHK. BY			