



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	4.25	6.94	5.5	2.8	1.75	0.91	2.50	2.74	0.79	1.6	5.8
	UT-2-SR		8.02	8.2	3.7				3.82	0.79	2.1	10.6
3/4"	UT-1-DA	4.62	7.54	6.4	3.2	1.94	1.08	2.50	3.17	0.79	1.8	7.5
	UT-2.5-SR		8.64	9.4	4.2				4.27	0.79	2.3	13.7
1"	UT-1-DA	5.00	8.07	6.4	3.2	2.12	1.61	2.50	3.17	0.79	1.8	8.2
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	14.4
1 1/2"	UT-2-DA	6.50	9.03	8.2	3.7	2.50	2.42	2.00	3.82	0.79	2.1	24.6
	UT-3-SR		9.99	10.7	4.8				4.78	0.79	2.7	33.4
2"	UT-3-DA	7.00	10.37	10.7	4.8	3.00	2.80	2.00	4.78	0.79	2.7	42.1
	UT-5-SR		13.38	20.6	7.4				7.40	1.18	3.9	87.8
3"	UT-3.5-DA	8.00	14.62	12.9	5.4	3.75	4.37	3.50	5.57	1.18	2.9	80.1
	UT-5-SR		16.45	20.6	7.4				7.40	1.18	3.9	116
4"	UT-5-DA	9.00	17.78	20.6	7.4	4.50	5.70	3.50	7.40	1.18	3.9	147
	UT-6-SR		19.79	22.6	8.6				9.41	1.18	4.3	215
6"	UT-6-DA	15.50	22.19	22.6	8.6	5.50	7.60	4.00	9.41	1.18	4.3	263
	UT-7-SR		25.81	26.5	11.4				13.03	1.18	5.7	388
8"	UT-7-DA	18.00	28.00	26.5	11.4	6.75	9.79	4.00	13.03	1.18	5.7	457

DIFF. PRESSURE ACROSS VALVE=285PSI
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)
 VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"-4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-8" FULL PORT SER. 5000F
 UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____



MARWINVALVE

a division of Richards Industries
 CINCINNATI, OHIO U.S.A
www.marwinvalve.com

DR. BY	DW	01/08/03	MD05009
CHK. BY			