



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	5.50	6.94	5.5	2.8	1.88	0.91	2.50	2.74	0.79	1.6	6.7
	UT-2-SR		8.02	8.2	3.7				3.82	0.79	2.1	11.5
3/4"	UT-0-DA	6.00	7.11	5.5	2.8	2.31	1.08	2.50	2.74	0.79	1.6	8.2
	UT-2-SR		8.19	8.2	3.7				3.82	0.79	2.1	13.0
1"	UT-1-DA	6.50	8.07	6.4	3.2	2.44	1.61	2.50	3.17	0.79	1.8	11.4
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	17.6
1 1/2"	UT-1-DA	7.50	8.07	6.4	3.2	3.06	2.11	2.00	3.17	0.79	1.8	22.8
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	29.0
2"	UT-2-DA	8.50	9.03	8.2	3.7	3.25	2.42	2.00	3.82	0.79	2.1	28.6
	UT-3-SR		9.99	10.7	4.8				4.78	0.79	2.7	37.4
3"	UT-3-DA	11.12	12.89	10.7	4.8	4.12	3.82	3.50	4.78	0.79	2.7	68.6
	UT-5-SR		15.90	20.6	7.4				7.40	1.18	3.9	111
4"	UT-3.5-DA	12.00	15.25	12.9	5.4	5.00	5.00	3.50	5.57	1.18	2.9	107
	UT-5-SR		17.08	20.6	7.4				7.40	1.18	3.9	143
6"	UT-5-DA	15.88	18.80	20.6	7.4	6.25	6.22	4.00	7.40	1.18	3.9	227
	UT-6-SR		20.81	22.6	8.6				9.41	1.18	4.3	295
8"	UT-6-DA	16.50	21.87	22.6	8.6	7.50	7.28	4.00	9.41	1.18	4.3	338
	UT-7-SR		25.49	26.5	11.4				13.03	1.18	5.7	463
10"	UT-7-DA	18.00	27.38	26.5	11.4	8.75	9.17	4.00	13.03	1.18	5.7	569

DIFF. PRESSURE ACROSS VALVE=740PSI
SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-10" RED. PORT SER. 6000R
UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____

 **MARWINVALVE**
 a division of Richards Industries
 CINCINNATI, OHIO U.S.A
 www.marwinvalve.com

DR. BY	DW	01/21/11	MD06011
CHK. BY			