



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	5.50	6.94	5.5	2.8	1.88	0.91	2.50	2.74	0.79	1.6	6.7
	UT-2-SR		8.02	8.2	3.7				3.82	0.79	2.1	11.5
3/4"	UT-1-DA	6.00	7.54	6.4	3.2	2.31	1.08	2.50	3.17	0.79	1.8	9.2
	UT-2.5-SR		8.64	9.4	4.2				4.27	0.79	2.3	15.4
1"	UT-1-DA	6.50	8.07	6.4	3.2	2.44	1.61	2.50	3.17	0.79	1.8	11.4
	UT-2.5-SR		9.17	9.4	4.2				4.27	0.79	2.3	17.6
1 1/2"	UT-2-DA	7.50	9.03	8.2	3.7	3.06	2.42	2.00	3.82	0.79	2.1	31.6
	UT-3-SR		9.99	10.7	4.8				4.78	0.79	2.7	40.4
2"	UT-3-DA	8.50	10.37	10.7	4.8	3.25	2.80	2.00	4.78	0.79	2.7	47.1
	UT-5-SR		13.38	20.6	7.4				7.40	1.18	3.9	92.8
3"	UT-3.5-DA	11.12	14.62	12.9	5.4	4.12	4.37	3.50	5.57	1.18	2.9	89.1
	UT-5-SR		16.45	20.6	7.4				7.40	1.18	3.9	125
4"	UT-5-DA	12.00	17.78	20.6	7.4	5.00	5.70	3.50	7.40	1.18	3.9	155
	UT-6-SR		19.79	22.6	8.6				9.41	1.18	4.3	223
6"	UT-6-DA	15.88	22.19	22.6	8.6	6.25	7.60	4.00	9.41	1.18	4.3	273
	UT-7-SR		25.81	26.5	11.4				13.03	1.18	5.7	398
8"	UT-7-DA	19.75	28.00	26.5	11.4	7.50	9.79	4.00	13.03	1.18	5.7	477

DIFF. PRESSURE ACROSS VALVE=740PSI
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}$ "
OTHER VA. DIM.: \leq NPS 2", $\pm \frac{1}{8}$ ";
NPS 2 $\frac{1}{2}$ "-4", $\pm \frac{1}{4}$ "; >4", $\pm \frac{1}{2}$ "
VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}$ "

CUSTOMER ORDER # _____
CUSTOMER _____
TAG No. _____
SIZE & MODEL # 1/2"-8" FULL PORT SER. 6000F
UT (NEW STYLE) ACT, @80PSI PRESSURE
CERTIFIED _____ DATE _____

 **MARWINVALVE**
a division of Richards Industries
CINCINNATI, OHIO U.S.A
www.marwinvalve.com

DR. BY	DW	02/20/03	MD06012
CHK. BY			