


SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-1-DA	4.35	7.66	6.4	3.2	1.58	1.20	2.50	3.17	0.79	1.8	14.6
	UT-3-SR		9.27	10.7	4.8				4.78	0.79	2.7	28.2
3/4"	UT-2.5-DA	4.75	8.67	9.4	4.2	1.92	1.61	2.00	4.27	0.79	2.3	22.9
	UT-3.5-SR		10.36	12.9	5.4				5.57	1.18	2.9	38.5
1"	UT-2.5-DA	5.50	8.87	9.4	4.2	2.16	1.81	2.00	4.27	0.79	2.3	29.7
	UT-4-SR		11.03	14.4	5.8				6.04	1.18	3.2	45.2
1 1/4"	UT-3.5-DA	6.70	11.12	12.9	5.4	2.65	2.37	2.00	5.57	1.18	2.9	51.9
	UT-5-SR		12.95	20.6	7.4				7.40	1.18	3.9	88.0
1 1/2"	UT-4-DA	6.70	11.59	14.4	5.8	2.65	2.37	2.00	6.04	1.18	3.2	56.4
	UT-6-SR		16.96	22.6	8.6			4.00	9.41	1.18	4.3	145.6
2"	UT-5-DA	7.87	13.16	20.6	7.4	2.95	2.58	2.00	7.40	1.18	3.9	89.0
	UT-6-SR		17.17	22.6	8.6			4.00	9.41	1.18	4.3	156.6

DIFF. PRESSURE ACROSS VALVE=4000PSI
SEAT MATERIAL-PEEK

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-2" FULL PORT SER. 10000
 FNPT, W/UT (NEW STYLE) ACT, @80PSI PRESS
 CERTIFIED _____ DATE _____

 MARWIN Ball Valves			RICHARDS INDUSTRIES 3170 Wasson Rd. Cincinnati, Ohio 45209 Telephone (513) 533-5600 Fax (513) 533-7343		
			DR. BY	DW	01/10/03
CHK.BY					