



SIZE	ACTUATOR	DIMENSIONS (INCHES)						WT.(LBS)
		A	B	C	D	E	F	
1"	ER-2-5-4	5.00	10.13	6.88	4.25	2.12	3.0	
1 1/2"	ER-4-10-4	6.50	12.01	7.00	7.00	3.00	4.0	
2"	ER-6-15-4	7.00	11.82	7.00	7.00	3.00	4.0	33
3"	ER-15-30-4	8.00	14.43	7.00	7.00	3.75	4.0	50
4"	ER-20-12-4	9.00	17.02	10.00	10.00	4.50	6.0	85

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}$ "

OTHER VA. DIM.: \leq NPS 2", $\pm \frac{1}{8}$ ";

NPS $2\frac{1}{2}$ "~4", $\pm \frac{1}{4}$ "; >4", $\pm \frac{1}{2}$ "

VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}$ "

DIFF. PRESSURE ACROSS VALVE=275PSI

SEAT MATERIAL-RPTFE

DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE.

CUSTOMER ORDER # _____

CUSTOMER _____

TAG No. _____

SIZE & MODEL # 1"-4" REDUCED PORT SER. 2000R

ER ELECTRIC ACTUATOR

CERTIFIED _____ DATE _____

 **MARWINVALVE**

a division of Richards Industries

CINCINNATI, OHIO

U.S.A

www.marwinvalve.com

DR. BY DW 01/21/11

CHK.BY _____

MD02016