


SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1"	UT-0-DA	5.00	7.20	5.5	2.8	2.13	1.67	2.00	2.74	0.79	1.6	12.9
	UT-2-SR		8.28	8.2	3.7				3.82	0.79	2.1	17.5
1 1/2"	UT-1-DA	6.50	8.18	6.4	3.2	2.50	2.22	2.00	3.17	0.79	1.8	17.7
	UT-2.5-SR		9.28	9.4	4.2				4.27	0.79	2.3	23.4
2"	UT-2-DA	7.00	9.23	8.2	3.7	3.00	2.62	2.00	3.82	0.79	2.1	25.8
	UT-3-SR		10.19	10.7	4.8				4.78	0.79	2.7	34.2
3"	UT-3-DA	8.00	12.80	10.7	4.8	3.75	3.73	3.50	4.78	0.79	2.7	47.4
	UT-4.5-SR (A)		15.31	16.9	6.5				6.90	1.18	3.4	70.3
4"	UT-3.5-DA	9.00	14.46	12.9	5.4	4.51	4.21	3.50	5.57	1.18	2.9	71.9
	UT-5-SR		16.29	20.6	7.4				7.40	1.18	3.9	108

DIFF. PRESSURE ACROSS VALVE=275PSI
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)
VA. END-TO-END LENGTH: $\pm \frac{1}{16}$ "
OTHER VA. DIM.: \leq NPS 2", $\pm \frac{1}{8}$ ";
NPS 2 1/2"~4", $\pm \frac{1}{4}$ "; >4", $\pm \frac{1}{2}$ "
VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}$ "

CUSTOMER ORDER # _____
CUSTOMER _____
TAG No. _____
SIZE & MODEL # 2"-4" REDUCED PORT SER. 2000R
UT (NEW STYLE) ACT, @80PSI PRESSURE
CERTIFIED _____ DATE _____



MARWINVALVE

a division of Richards Industries
CINCINNATI, OHIO U.S.A
www.marwinvalve.com

DR. BY	DW	01/24/11	MD02043
CHK. BY			