



- ① MANUAL OVER-RIDE HANDWHEEL PROVIDED ON ACTUATORS ER-6-15-4, ER-10-15-4, AND ER-15-30-4 (TOP ONLY).
- ② MANUAL OVER-RIDE HANDWHEEL PROVIDED ON ACTUATOR ER-50-68-4 (SIDE ONLY).

SIZE	ACTUATOR	DIMENSIONS (INCHES)							WT.(LBS)
		A	B	C	D	E	F	G	
1/2"	ER-2-5-4	4.25	9.08	6.88	4.25	1.75	-	3.0	10
3/4"	ER-2-5-4	4.63	9.24	6.88	4.25	1.94	-	3.0	17
1"	ER-2-5-4	5.00	9.62	6.88	4.25	2.12	-	3.0	19
1 1/2"	ER-6-15-4	6.50	11.20	7.00	7.00	2.50	-	4.0	32
2"	ER-6-15-4	7.00	11.77	7.00	7.00	3.00	-	4.0	38
2 1/2"	ER-10-15-4	7.50	12.56	7.00	7.00	3.50	-	4.0	49
3"	ER-15-30-4	8.00	14.54	7.00	7.00	3.75	-	4.0	63
4"	ER-15-30-4	9.00	15.26	7.00	7.00	4.50	-	4.0	82
6"	ER-50-68-4	15.50	24.61	14.00	12.90	5.50	4.31	7.0	288

MAX. DIFF. PRESSURE ACROSS VALVE

SEAT MATERIAL-RPTFE

DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE.

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH:  $\pm \frac{1}{16}$ "

OTHER VA. DIM.:  $\leq$ NPS 2",  $\pm \frac{1}{8}$ ";

NPS 2 1/2"~4",  $\pm \frac{1}{4}$ "; >4",  $\pm \frac{1}{2}$ "

VA.-ACT. ASSY & PIPING DIM.:  $\pm \frac{1}{2}$ "

CUSTOMER ORDER # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

TAG No. \_\_\_\_\_

SIZE & MODEL # 1/2"-6" FULL PORT SER. 2000F  
ER ELECTRIC ACTUATOR

CERTIFIED \_\_\_\_\_ DATE \_\_\_\_\_

**MARWINVALVE**

a division of Richards Industries

CINCINNATI, OHIO

U.S.A

www.marwinvalve.com

DR. BY	DW	10/01/13
CHK. BY		

MD02017