



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	4.25	7.23	5.5	2.8	1.75	1.70	2.00	2.74	0.79	1.6	11.6
	UT-1-SR		7.66	6.4	3.2				3.17	0.79	1.8	12.8
3/4"	UT-0-DA	4.63	7.39	5.5	2.8	1.94	1.86	2.00	2.74	0.79	1.6	12.6
	UT-2-SR		8.47	8.2	3.7				3.82	0.79	2.1	16.9
1"	UT-0-DA	5.00	7.77	5.5	2.8	2.12	2.24	2.00	2.74	0.79	1.6	14.5
	UT-2-SR		8.85	8.2	3.7				3.82	0.79	2.1	19.3
1 1/2"	UT-2-DA	6.50	9.07	8.2	3.7	2.50	2.46	2.00	3.82	0.79	2.1	23.8
	UT-3-SR		10.03	10.7	4.8				4.78	0.79	2.7	32.7
2"	UT-2-DA	7.00	9.64	8.2	3.7	3.00	3.03	2.00	3.82	0.79	2.1	30.8
	UT-3.5-SR		11.78	12.9	5.4				5.57	1.18	2.9	47.5
2 1/2"	UT-2.5-DA	7.50	10.88	9.4	4.2	3.50	3.82	2.00	4.27	0.79	2.3	42.8
	UT-3.5-SR		12.57	12.9	5.4				5.57	1.18	2.9	58.8
3"	UT-3-DA	8.00	13.37	10.7	4.8	3.75	4.30	3.50	4.78	0.79	2.7	60.5
	UT-4.5-SR		15.88	16.9	6.5				6.90	1.18	3.4	94
4"	UT-3.5-DA	9.00	15.27	12.9	5.4	4.50	5.02	3.50	5.57	1.18	2.9	86.2
	UT-5-SR		17.10	20.6	7.4				7.40	1.18	3.9	133
6"	UT-5-DA	15.50	17.69	20.6	7.4	5.50	5.11	4.00	7.40	1.18	3.9	231
	UT-6-SR		19.70	22.6	8.6				9.41	1.18	4.3	300

MAX DIFF. PRESSURE ACROSS VALVE  
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH:  $\pm \frac{1}{16}$ "  
OTHER VA. DIM.:  $\leq$ NPS 2",  $\pm \frac{1}{8}$ ";  
NPS 2 1/2"~4",  $\pm \frac{1}{4}$ "; >4",  $\pm \frac{1}{2}$ "  
VA.-ACT. ASSY & PIPING DIM.:  $\pm \frac{1}{2}$ "

CUSTOMER ORDER # \_\_\_\_\_  
CUSTOMER \_\_\_\_\_  
TAG No. \_\_\_\_\_  
SIZE & MODEL # 1/2"-6" FULL PORT SER. 2000F  
UT (NEW STYLE) ACT, @80PSI PRESSURE \_\_\_\_\_  
CERTIFIED \_\_\_\_\_ DATE \_\_\_\_\_



**MARWIN**  
Ball Valves

RICHARDS INDUSTRIES  
3170 Wasson Rd.  
Cincinnati, Ohio 45209  
Telephone (513) 533-5600  
Fax (513) 533-7343

DR. BY	DW	10/01/13
CHK. BY		

**MD02042**