



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/2"	UT-0-DA	5.51	8.05	5.5	2.8	1.87	1.52	3.00	2.74	0.79	1.6	8.6
	UT-1-SR		8.48	6.4	3.2				3.17	0.79	1.8	10.3
3/4"	UT-0-DA	5.98	8.05	5.5	2.8	2.31	1.52	3.00	2.74	0.79	1.6	11.3
	UT-1-SR		8.48	6.4	3.2				3.17	0.79	1.8	13.0
1"	UT-1-DA	6.50	8.76	6.4	3.2	2.44	1.80	3.00	3.17	0.79	1.8	15.2
	UT-2-SR		9.41	8.2	3.7				3.82	0.79	2.1	19.0
1 1/2"	UT-2-DA	7.48	10.51	8.2	3.7	3.07	2.40	3.50	3.82	0.79	2.1	27.2
	UT-3-SR		11.47	10.7	4.8				4.78	0.79	2.7	36.1
2"	UT-2-DA	8.50	11.03	8.2	3.7	3.25	2.92	3.50	3.82	0.79	2.1	31.7
	UT-3.5-SR		13.17	12.9	5.4				5.57	1.18	2.9	50.5
3"	UT-3.5-DA	11.14	13.81	12.9	5.4	4.13	4.06	3.00	5.57	1.18	2.9	78.6
	UT-5-SR		15.64	20.6	7.4				7.40	1.18	3.9	118.3
4"	UT-3.5-DA	12.00	14.75	12.9	5.4	5.00	5.00	3.00	5.57	1.18	2.9	118.6
	UT-5-SR		16.58	20.6	7.4				7.40	1.18	3.9	154.8
6"	UT-6-DA	15.87	21.76	22.6	8.6	6.25	7.17	4.00	9.41	1.18	4.3	252.3
	UT-7-SR		25.65	26.5	11.4				13.3	1.18	5.7	374.0

DIFF. PRESSURE ACROSS VALVE = 740PSI.
SEAT MATERIAL-RPTFE

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/2"-6" FULL PORT SER. 6801F
UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____



MARWIN
Ball Valves

RICHARDS INDUSTRIES
3170 Wasson Rd.
Cincinnati, Ohio 45209
Telephone (513) 533-5600
Fax (513) 533-7343

DR. BY DW 12/14/07
 CHK. BY _____

MD06047