



SIZE	ACTUATOR	DIMENSIONS (INCHES)											WT (LBS)
		A	B	C	D	E	F	G	H	J	K	L	
1/4" & 3/8"	UT-0-DA	2.68	6.59	5.5	2.8	0.63	1.06	1.34	2.74	0.79	1.6	2.00	9.2
	UT-1-SR		7.02	6.4	3.2				3.17	0.79	1.8		13.8
1/2"	UT-0-DA	2.95	6.73	5.5	2.8	0.74	1.20	1.48	2.74	0.79	1.6	2.00	9.2
	UT-2-SR		7.81	8.2	3.7				3.82	0.79	2.1		16.7
3/4"	UT-1-DA	3.39	7.41	6.4	3.2	0.94	1.45	1.69	3.17	0.79	1.8	2.00	11.2
	UT-2-SR		8.06	8.2	3.7				3.82	0.79	2.1		17.3
1"	UT-2-DA	4.08	8.16	8.2	3.7	1.10	1.55	2.03	3.82	0.79	2.1	2.00	15.5
	UT-3-SR		9.12	10.7	4.8				4.78	0.79	2.7		23.5
1 1/4"	UT-2-DA	4.53	8.32	8.2	3.7	1.26	1.71	2.26	3.82	0.79	2.1	2.00	15.8
	UT-3-SR		9.28	10.7	4.8				4.78	0.79	2.7		24.6
1 1/2"	UT-2-DA	4.92	8.74	8.2	3.7	1.53	2.13	2.46	3.82	0.79	2.1	2.00	17.8
	UT-3.5-SR		10.88	12.9	5.4				5.57	1.18	2.9		32.2
2"	UT-2.5-DA	5.75	9.51	9.4	4.2	1.88	2.48	2.87	4.27	0.79	2.3	2.00	28.2
	UT-3.5-SR		11.23	12.9	5.4				5.57	1.18	2.9		33.5

MAX. DIFF. PRESSURE ACROSS VALVE
SEAT MATERIAL-RPTFE

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: $\pm \frac{1}{16}"$
 OTHER VA. DIM.: $\leq \text{NPS } 2", \pm \frac{1}{8}"$;
 NPS $2 \frac{1}{2}" \sim 4", \pm \frac{1}{4}"$; $> 4", \pm \frac{1}{2}"$
 VA.-ACT. ASSY & PIPING DIM.: $\pm \frac{1}{2}"$

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4"-2" 3T-37R/3L-38R
 RED. PORT W/UT (NEW STYLE) ACT, @80PSI PRES.
 CERTIFIED _____ DATE _____



a division of Richards Industries

CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DR. BY DW 02/02/11
 CHK. BY

MD03093