



1 MANUAL OVER-RIDE HANDWHEEL PROVIDED ONLY ON ACTUATOR ER-4-10-4 (ON TOP).

SIZE	ACTUATOR	DIMENSIONS (INCHES)							WT.(LBS)
		A	B	C	D	E	F	G	
1/4"	ER-1-2-4	2.63	5.70	5.63	4.00	0.67	1.31	2.5	6
3/8"	ER-1-2-4	2.63	5.70	5.63	4.00	0.67	1.31	2.5	6
1/2"	ER-1-2-4	2.87	5.70	5.63	4.00	0.67	1.43	2.5	6
3/4"	ER-1-2-4	3.18	5.78	5.63	4.00	0.80	1.59	2.5	7
1"	ER-2-5-4	3.74	7.01	6.88	4.25	0.94	1.87	2.5	10
1 1/4"	ER-2-5-4	4.38	7.23	6.88	4.25	1.18	2.20	3.0	12
1 1/2"	ER-2-5-4	4.86	7.72	6.88	4.25	1.42	2.43	3.0	16
2"	ER-4-10-4	5.70	11.79	7.00	7.00	1.69	2.90	4.0	31

MAX. DIFF. PRESSURE ACROSS VALVE
 SEAT MATERIAL-RPTFE
 DIMENSIONS GIVEN FOR NEMA 4 ENCLOSURE

TOL. UNLESS OTHERWISE NOTED (IN.)
 VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4"-2" REDUCED PORT 3T-33R/
3L-34R W/ER ELECTRIC ACTUATOR
 CERTIFIED _____ DATE _____



MARWINVALVE

a division of Richards Industries
 CINCINNATI, OHIO U.S.A
www.marwinvalve.com

DR. BY	DW	02/02/11	MD03104
CHK.BY			