



SIZE	ACTUATOR	DIMENSIONS (INCHES)										WT (LBS)
		A	B	C	D	E	F	G	H	J	K	
1/4"	UT-0-DA	2.50	6.00	5.5	2.8	0.90	0.62	1.85	2.74	0.79	1.6	8.2
	UT-1-SR		6.43	6.4	3.2				3.17	0.79	1.8	
3/8"	UT-0-DA	2.50	6.00	5.5	2.8	0.90	0.62	1.85	2.74	0.79	1.6	8.2
	UT-1-SR		6.43	6.4	3.2				3.17	0.79	1.8	
1/2"	UT-0-DA	2.50	6.00	5.5	2.8	0.90	0.62	1.85	2.74	0.79	1.6	10.2
	UT-1-SR		6.43	6.4	3.2				3.17	0.79	1.8	
3/4"	UT-0-DA	3.00	6.13	5.5	2.8	0.97	0.75	1.85	2.74	0.79	1.6	10.2
	UT-1-SR		6.56	6.4	3.2				3.17	0.79	1.8	
1"	UT-1-DA	3.69	6.65	6.4	3.2	1.25	0.84	1.85	3.17	0.79	1.8	10.7
	UT-2.5-SR		7.75	9.4	4.2				4.27	0.79	2.3	
1 1/4"	UT-2-DA	4.09	7.87	8.2	3.7	1.34	1.00	2.26	3.82	0.79	2.1	13.7
	UT-3-SR		8.83	10.7	4.8				4.78	0.79	2.7	
1 1/2"	UT-2-DA	4.56	8.08	8.2	3.7	1.50	1.19	2.28	3.82	0.79	2.1	15.0
	UT-3-SR		9.04	10.7	4.8				4.78	0.79	2.7	
2"	UT-2-DA	6.16	8.05	8.2	3.7	2.00	1.56	2.50	3.82	0.79	2.1	21.8
	UT-3.5-SR		10.81	12.9	5.4				5.57	1.18	2.9	
2 1/2"	UT-2.5-DA	6.84	9.45	9.4	4.2	2.50	1.94	2.45	4.27	0.79	2.3	34.0
	UT-3.5-SR		11.14	12.9	5.4				5.57	1.18	2.9	

TOL. UNLESS OTHERWISE NOTED (IN.)

VA. END-TO-END LENGTH: ± 1/16"
 OTHER VA. DIM.: ≤NPS 2", ± 1/8";
 NPS 2 1/2"~4", ± 1/4"; >4", ± 1/2"
 VA.-ACT. ASSY & PIPING DIM.: ± 1/2"

DIFF. PRESSURE ACROSS VALVE=600PSI

SEAT MATERIAL-TEFLON

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4"-2 1/2" FULL PORT 4600F
W/UT (NEW STYLE) ACT, @80PSI PRESSURE
 CERTIFIED _____ DATE _____



MARWIN
 Ball Valves

RICHARDS INDUSTRIES
 3170 Wasson Rd.
 Cincinnati, Ohio 45209
 Telephone (513) 533-5600
 Fax (513) 533-7343

DR. BY	DW	03/20/03
CHK. BY		

MD04001