



SIZE	DIMENSIONS (INCHES)						BREAKAWAY TORQUE
	A	B	C	D	ØE	ØF	
1/4"	2.63	0.93	0.27	0.35	1.42	0.21	38 in-lbs.
3/8"	2.63	0.93	0.27	0.35	1.42	0.21	38 in-lbs.
1/2"	2.63	0.93	0.27	0.35	1.42	0.21	38 in-lbs.
3/4"	2.99	1.00	0.27	0.35	1.42	0.21	45 in-lbs.
1"	3.34	1.34	0.35	0.35	1.42	0.21	53 in-lbs.
1 1/4"	3.66	1.48	0.35	0.35	1.42	0.21	* in-lbs.
1 1/2"	4.13	1.98	0.42	0.43	1.97	0.25	* in-lbs.
2"	4.80	2.18	0.42	0.43	1.97	0.25	120 in-lbs.
2 1/2"	6.10	2.75	0.59	0.55	2.76	0.33	* in-lbs.
3"	6.88	3.13	0.59	0.55	2.76	0.33	* in-lbs.
4"	8.04	3.86	0.70	0.66	2.76	0.33	* in-lbs.

TOL. UNLESS OTHERWISE NOTED (IN.)
 VA. END-TO-END LENGTH: $\frac{1}{8}$ "
 OTHER VA. DIM.: \leq NPS 2", $\frac{1}{16}$ "
 NPS $2\frac{1}{2}$ "-4", $\frac{1}{4}$ "; >4", $\frac{1}{8}$ "
 VA-ACT. ASSY & PIPING DIM.: $\frac{1}{2}$ "

CUSTOMER ORDER # _____
 CUSTOMER _____
 TAG No. _____
 SIZE & MODEL # 1/4" - 4" FULL PORT DM600, BRASS
W/ FNPT/FSW ENDS
 CERTIFIED _____ DATE _____



a division of Richards Industries
 CINCINNATI, OHIO U.S.A

www.marwinvalve.com

DRAWN BY	DATE
DW	6/24/08
CHECKED BY	DATE

MD60016